Tas

& SIDESPRAY w/ 48" FLEX HOSE

T&S BRASS AND BRONZE WORKS, INC.

2 SADDLEBACK COVE / P.O. BOX 1088 / TRAVELERS REST, SC 29690 PHONE 800-476-4103 - FAX 864-834-3518

Model No.

B - 1157

RELIABILITY BUILT IN

BUILT IN Architect/Engineer Approval: Job Name: Notes: 8" ELBOW TO CONNECT HOSE [203mm] DOWN BEHIND WALL 1/2" NPT MALE SHANKS -1" [25mm] [25mm] MOUNTING SURFACE 1/4" [6mm] MAX. MOUNTING SURFACE THICKNESS LEVER HANDLES w/ COLOR CODED INDEXES [203mm] OPENING FAUCET PRESSURIZES HOSE. FOR FULL HOSE PRESSURE, TURN 4-ARM HANDLE UNTIL IT POPS-UP, STOPPING WATER 5 3/8" FLOW THROUGH NOZZLE. [136mm] 4 3/8" SWIVEL JOINT [111mm] 2" 002857-40 [51mm] SELF-CLOSING 1 3/8" [35mm] SPRAY -10 1/2" [267mm] B-LT STREAM REGULATOR MOUNTING SURFACE 150A B-KF DECK Tailpiece and Nut FLANGE -Furnished for 1/4" NPT Connection -013E-48H 48" FLEXIBLE STAINLESS STEEL HOSE -NOTE: ROUGH-IN REQUIREMENT (3) Ø1" [25mm] MOUNTING HOLES Product Description: Drawn: Checked Scale: 8" c/c WALL MOUNT WORKBOARD FAUCET w/ LEVER KJG DHL 1:4 HANDLES, 8" SWING NOZZLE, 1/2" NPT MALE SHANKS, Approved Date:

JHB

02/3/12